

BUMPUS & JONES
Advertising-Sales Promotion-Public Relations

Photo & Press Release Summary

Release # 22-005

Date September 11, 1972

Subject NEW LOW COST DATANETICS KEYBOARD SWITCH

Released for: Datanetics Corp., Fountain Valley, Calif.

Distribution:

Aerospace Daily
Astronautics & Aeronautics
Aviation Daily
Aviation Week & Space Technology
GSE
Interavia Magazine
Canadian Aviation

Electrical Equipment
Electric Light & Power
Information Display
Circuits Manufacturing
Computer Design
EDN/EEE
Electromechanical Design
Electronic Buyers' News
Electro Procurement
Electronic Component News
Electronic Design
The Electronic Engineer
Electronic News
Electronic Packaging and Production
Electronic Products
Electronics
Evaluation Engineering
Telephone Engineer & Management
Appliance Engineer
Canadian Electronics Engineering
Electrical Equipment News
Electron

Industrial Distribution
Industrial Equipment News
New Equipment News
Southern California Industrial News
Western Industrial News
Design News
Machine Design
Product Design & Development

Product Engineering
Mechanical Engineering
Canadian Industrial Equipment News
Design Engineering
New Equipment News
California Industry
Equipment Reporter

Computer
Computer & Automation
Computer Components News
Computerworld
Instrument & Apparatus News
Instruments & Control Systems
Canadian Controls & Instrumentation
Control Engineering

Purchasing Magazine
Purchasing World
Modern Purchasing

VIP List
Shareholders List

NEWS RELEASE

BUMPAS & JONES • 2131 N. BROADWAY, SANTA ANA, CALIF. 92706

RELEASE: IMMEDIATE

CONTACT:

FOR: Datanetics Corporation

NEW LOW COST DATANETICS KEYBOARD SWITCH
FEATURES HYSTERESIS, SEALED SWITCH ELEMENT
AND CONVENTIONAL TYPING CHARACTERISTICS
FOR COMPUTER TERMINALS AND DESK TOP CALCULATORS

Fountain Valley, Calif. - September 14, 1972 - Built-in hysteresis to eliminate "teasing", environmentally sealed elastic diaphragm switch element and negligible bounce are prime features of a low-profile, low-cost keyboard switch announced by Datanetics Corporation. Designated the Series DC-50 "Key Switch"*, the unit has the conventional typing stroke, force characteristics and other operating features usually found only in magnetic actuated switches; optional tactile response is offered to meet human factors requirements. The switch will interface with MOS/LSI and standard DTL/TTL circuitry in computer peripheral terminals and desk top calculator applications.

The DC-50 Key Switch has a 1 Form A (N. O.) contact arrangement, with a rating of 0.3 to 30 mw. It features a switching voltage range of 500 mv to 30 v., at 0.3 to 10 ma. (resistive). Capacitance is typically less than 5 pf, at 1 KHz. Life is stated in excess of 50,000,000 operations, at rated load; operating temperature range is +32^oF to +140^oF. Height is 1.150" (1.250", with key cap), and minimum 0.625" center-to-center key spacing permits higher density installations. An alternate action version is also available.

The elastic diaphragm switch element is permanently sealed, using thermoset adhesives. The diaphragm materials (Kapton), as well as that for the key guide

-more-

*Patent Pending

housing, have been selected to withstand the severe temperature requirements of actual submersion during flow soldering processes. Contacts and terminals are copper with gold-over-nickel plating.

Manufacturer: Datanetics Corporation
18065 Euclid Street
Fountain Valley, Calif. 92708
Tel: (714) 549-1191

Price: \$0.31 ea., in 1,000,000 pc. lot.

Availability: 4-6 wks, ARO

