


**Fujitsu
Reed Products**

Reed Low-Profile Keyswitches

FES-9 Series

Best choice today in meeting demanding keyboard applications!!



- Available in either "light touch" (snap-action) or "regular touch" models
- Choice of momentary or alternate action
- Wide range of keyface style and mounting (including sloped, stepped and sculptured)


FUJITSU LIMITED
Communications and Electronics

Circle 185 on reader service card

Reed Precision Switches

FPS-300 Series

Highest dependability of operation!!



- Longer and more uniform service life for improved cost-performance
- 1 Form A or 1 Form B
- 30W DC contact rating available
- Wide choice of actuator with positive snap-action
- 10⁶ operations min.
- Wide range of ambient atmospheric conditions (-10°~60°C, -30°~70°C)

FUJITSU LIMITED
Communications and Electronics

* For contact information see page 154

Circle 152 on reader service card

New products

ties would have a delivery time of six to 10 weeks.

Micro Networks Corp., 324 Clark St., Worcester, Mass. 01606. Phone John F. Munn at (617) 852-5400 [382]

LED display interfaces
directly with computers

An intelligent alphanumeric light-emitting-diode display offers full buffering, a built-in ASCII decoder, multiplexer, memory, and light-emitting-diode drivers. The device is thus able to interface with microcomputers and other logic circuits exactly as a random-access memory does. Any character position may be accessed independently and asynchronously. Characters remain lit until a new one is entered.

The DL-1416 display generates all 64 ASCII characters 0.16 inch high. It is actuated entirely by TTL levels and requires only a single 5-volt supply. Each module displays four characters and is so designed that any number of modules may be butted end-to-end to create long displays with equal spacing between all characters. The modules measure 1 by 1.2 inches.

In quantities of 1,000, price is \$5.50 per character (\$22 per four-character module). Delivery is from stock.

Litronix, 19000 Homestead Road, Cupertino, Calif. 95014. Phone (408) 257-7910 [384]

Compact 12-bit d-a converter
includes an input buffer

Designed to help engineers solve the interfacing problem with minicomputers and microcomputers, the DAC-HK12B series of 12-bit digital-to-analog converters includes a 12-bit input storage register. A control input determines the state of the d-a converter, having it either store or transfer the input data.

The thin-film hybrid device incorporates a zener reference circuit, a reference-control circuit, three quad current switches, a fast output

Hipotronics inc. HIGH VOLTAGE DC POWER SUPPLIES AND POWER PACKS

Standard supplies from
1 kW to 50 kW



1 kW supply
provides
120 kV @ 8 mA

Power Supplies

Complete range of unregulated high voltage dc supplies with voltage outputs from 1 kV to 1000 kV and current outputs from 10 mA to 50 Amps available in standard designs at economical prices. Fully instrumented and protected, these supplies are ideal for:

- Laboratory use
- Capacitor charging
- Laser supplies
- CRT supplies
- Marx generators
- Many more

5, 7.5 & 10 kV
@ 5 mA OEM
Power Packs



Power Packs

Miniaturized, oil-filled steel cans for OEM use. Voltages from 2.5 kV to 100 kV at 2, 5 & 10 mA. Low cost, high reliability.

Metered Power Packs

Same miniature power packs available with simplified or deluxe controls for rack-mounting. Short circuit current limit option makes these ideal for cap charging applications.

Write or call for complete details.

HIPOTRONICS

HIPOTRONICS, INC.

P O Drawer A. Brewster. NY 10509
(914) 279-8031 Twx 710-574-2420
Amex Symbol HIP

Circle 186 on reader service card