

STANDARD KEYBOARD

Reduced Footprint Keyboard

87-Keys (For Windows®95)

FKB8745 SERIES



■ FEATURES

- Compatible with AT and PS/2
- Supports Windows®95 keyboard function
- Excellent operation
 - Curved keyswitch panel
 - Full-travel 3.8 mm keystroke, 55 gf operating force, 20 gf tactile response
 - Soft tactile feedback, ultra silent
- High quality and reliability
- Laser printed keycaps meet environmental requirements

■ MAIN APPLICATIONS

- Desktop type personal computer
- Workstation

■ CONSTRUCTION

- With enclosure and interface cable

FKB8745 SERIES

■ SPECIFICATIONS


Item		Specifications
Mechanical	Number of Keys	(1) U.S. : 87 keys
	Key Switch Type	Membrane switch
	Keytop	Rectangular cylindrical, Curved sculptured
	Operating Force	55 gf \pm 25 gf
	Stroke	3.8 mm \pm 0.5 mm
	Tactile	20 gf typ., Soft
	Operating Life	10 M operations min.
	Tilt	2 levels
Electrical	Power Supply	+5 V \pm 0.25 V DC, 100 mA max.
	Interface	Serial transmission (clock synchronous type) AT and PS/2 compatible
	Interlock	F-key rollover
	Connector	Mini-DIN 6 pin/DIN 5 pin
Environment	Operating Temperature	+10 to 50°C
	Storage Temperature	-10 to 60°C
	Humidity	90% RH max. at +40°C max. inversely proportional change to 50% RH at 60°C

■ PART NUMBERS

Please contact your local Sales Office for further Information.


■ CONNECTOR PIN ASSIGNMENT

Mini-DIN 6 pin




Pin number	Signal name
1	Data
2	—
3	GND (SG)
4	+5 V
5	Clock
6	—
SHELL	GND (FG)

DIN 5 pin




Pin number	Signal name
1	Clock
2	Data
3	—
4	GND (SG)
5	+5 V
SHELL	GND (FG)

■ OPERATING FORCE AND TRAVEL CHARACTERISTICS



■ DIMENSIONS



■ KEY LAYOUT

